



Combi Tool CT 4150 C

100163

i-Bolt Technology included:

- Much flatter design for better access into narrow spaces
- Squeezes blades together more tightly, resulting in less blade separation and improved cutting performance
- Stainless steel cover protects bolt

LED lighting in carrying handle:

- Never work in your own shadow again
- Have your own light source when rescue scene lighting is absent (e.g. in rapid intervention situations)
- LEDs work appr. 6 hours on 1 standard AA battery

Multifunctional rescue tool:

- For cutting spreading, squeezing and pulling (with the optional pulling accessories)

Safe and user-friendly deadman's handle:

- Only black part rotates
- Accurate spring return to neutral position
- Precise proportional operation
- Max. rotation to the right and to the left only 22°

Non-slip carrying handle:

- For a perfect grip under all circumstances

Connectable to all Holmatro pumps with CORE connection:

- The separate pump decreases the weight of the tool and increases maneuverability

For both left- and right handed operators:

- Easy operation in any position

Technical specifications

Details

Articlenumber	150.012.099	
Basic specifications		
model	CT 4150 C	
equipped with (connector type)	CORE	
max. working pressure	720 / 72 (bar/Mpa)	10443 psi
Performance		
max. spreading force	211 / 21.5 (kN/t)	47435 lbf
min. spreading force (EN 13204)	35 / 3.6 (kN/t)	7868 lbf
spreading distance	360 mm	14.2 in
max. cutting force C0	380 / 38.7 (kN/t)	85427 lbf
max. cutting opening	229 mm	9 in
max. squeezing force	76 / 7.7 (kN/t)	17085 lbf
max. pulling force	51 / 5.2 (kN/t)	
Dimensions, weight and temperature		
weight, ready for use	14.2 kg	31.3 lb
dimensions (AxBxC)	787 x 270 x 202 mm	31 x 10.6 x 8 in
Norms		
EN 13204 classification	CK 35/360 H-14.2	
NFPA 1936 compliant	yes	
EN 13204, cutting capacity	1I 2H 3H 4J 5H	
Cutting performance		
round bar (S235 acc. to EN 13204)	32 mm	1.3 in

