

Door Opener HDO 100 - 2

100194

Single-acting hydraulic door opener HDO 100 with 360° rotating swivel, 30 cm/1 ft pigtail hose and 360° rotatable carrying handle + hand pump PA 04 H 2 S + 3 m/9.8 ft single hose B 3 SOU in synthetic carrying / storage box.

Versatile:

- Opens every door that opens to the inside in less than 30 seconds, regardless of locks, door-chains or catches
- With 360° rotatable handle
- For optimal ease of installation
- With rotating hose connection

Technical specifications

Details			
Articlenumber	150.062.213	150.062.213	
Basic specifications	·		
model	HDO 100 - 2	HDO 100 - 2	
max. working pressure	720 / 72 (bar/Mpa)	10443 psi	
Performance	•	•	
max. spreading force	100 / 10.2 (kN/t)	22481 lbf	
stroke	130 mm	5.1 in	
capacity, spreading jack	100 / 10.2 (kN/t)	22481 lbf	
retracted length	300 mm	11.8 in	
extended length	430 mm	16.9 in	
Dimensions, weight and tem	perature		
weight, ready for use	14.2 kg	31.3 lb	
dimensions (AxBxC)	600 x 400 x 185 mm	23.6 x 15.7 x 7.3 in	





