

Double lanyard with integrated energy absorber Apsorbica-Y, Petzl

1029417

ABSORBICA®-Y is a double lanyard with compact energy absorber, designed for progression on a vertical structure or a horizontal lifeline, and for passing intermediate anchors. It functions with users weighing between 50 and 140 kg. It has several installation options on the harness and can be used with different types of connectors. It is available in two lengths: 80 or 150 cm versions (without connectors). The 150 cm version has elasticized arms to avoid hindering progression. Depending on the connectors used, ABSORBICA®-Y is certified to American, European, and Russian standards.

Description

- Designed for progression on a vertical structure or horizontal lifeline, and when passing intermediate anchors
 - Absorbs energy in the event of a fall:
- Tearing of the energy absorber webbing limits the impact force on the user
 - Works with users who weigh between 50 and 140 kg (1)
 - Progressive tearing reduces the deceleration on lightweight users
- Minimal bulk:
- Compact energy absorber facilitates handling
 - FLEX version with 150 cm of elasticized webbing to avoid hindering progression
- Durable fabric pouch with opening system at each end, protects the energy absorber from abrasion or contaminants while allowing for regular inspection of the absorber
 - Two options for installation on the harness, depending on use:
- Frequent connection/disconnection: with a carabiner held in correct position by the STRING positioning accessory (included with the lanyard)
 - Semi-permanent connection: using either a RING OPEN gated ring whose circular shape allows optimal positioning, or a SWIVEL OPEN to avoid tangling
- Two options for connectors at end of lanyard: carabiners or large-opening MGO OPEN connectors
 - Available in two lengths: 80 and 150 cm

Technical specifications

- Material(s): Polyester, nylon, high-modulus polyethylene

- Certification(s): CE EN 355 when used with EN 362, UKCA, EAC connectors (maximum certified mass: 100 kg), ANSI Z359.13 12 feet when used with ANSI Z359.12 connectors (maximum certified user weight: 140 kg)

References

References	L012AA00	L014AA01
Version	-	FLEX
Length without connectors	80 cm	150 cm
Connector	Without connector	Without connector
Length with connectors	90 to 130 cm, depending on the connectors (more information in the Instructions for Use and the technical tips at www.petzl.com)	160 to 200 cm, depending on the connectors (more information in the Instructions for Use and the technical tips at www.petzl.com)
Weight	370 g	430 g
Guarantee	3 years	3 years
Inner Pack Count	1	1



