

Electric Duo Pump SR 42 DC 2

100174

230 VAC electrically driven Spider range duo pump, CORE version, with 2 tool connections (MTO: simultaneous tool operation). Including hose reel on each side with 2 x 20 m orange hoses.

3-stage pump technology:

- Much higher flow/speed in 2nd stage for quicker rescue operations
- Lower flow/speed in 3rd stage for more tool control

Optimal weight / performance ratio:

- Lighter than comparable heavy duty pumps

Soft-grip carrying handle:

- Better grip
- Ergonomic design for improved carrying balance
- Pump easier to carry

Large hydraulic oil capacity:

- Enough oil to operate any two tools at the same time and multiple tools successively, including the biggest rams

Hydraulic oil level indicator on pump:

- Integrated dip stick for quick and easy monitoring of oil level

Technical specifications

Details		
Articlenumber	150.152.728	
Basic specifications		
model	SR 42 DC 2	
equipped with (connector type)	CORE	
max. working pressure	720 / 72 (bar/Mpa)	10443 psi
Performance		

number of stages	3	
capacity oil tank (effective)	6000 cc	202.9 oz
General specifications		
pump type	2 x 3-stage axial pump	
operator type	electric motor	
number of tool connections	2	
number of tools simultaneously usable	2	
engine	230 VAC - 1.8 kW - 50 Hz - 1 Ph	
length hoses on double hose reel	20 m	66 ft
hose colour left	orange	
hose colour right	orange	
required power	7.2 KVA	
Dimensions, weight and temperature		
weight, ready for use	70.1 kg	154.5 lb
dimensions (AxBxC)	866 x 552 x 507 mm	34.1 x 21.7 x 20 in
Norms		
EN 13204 classification	MTO	
NFPA 1936 compliant	yes	



