



## Fire extinguisher S50, ABC powder

1001073

The fire extinguisher activation system with a push-button is the fastest method of activation, without the risk of improper use.

The installed  $CO_2$  cartridge ensures the high reliability of the fire extinguisher through a long time, whereas the easy handling of nozzle at the end of the flexible rubber hose enables safe extinguishing of fires of all classes.

**USE:** If used, pull out a yellow safety pin and with a stroke or by pushing the button on the closure you will put the fire extinguisher under pressure, which prepares the fire extinguisher for extinguishing. A stream of powder needs to be directed at the base of the fire with pistol-nozzle, and where appropriate, stop the powder leakage.

**APPLICATION**: Due to their reliability, we recommend using the fire extinguihers with CO<sub>2</sub> cartridge in industrial plants and warehouses, residential properties, hotels, garages, and in means of transport. They can be successfully used for extinguishing all categories of fires except those involving burning metals an their alloys.

## **Technical specifications**

Device type	mobile with CO <sub>2</sub> cartridge
Type of extinguishing agent	Powder ABC
Fire class	ABC
Edition	Regular Edition
Extinguishing electrical equipment under voltage	up to 1000V
Extinguishing media quantity	50 kg
Workshop	CO <sub>2</sub> - 1100 g
Temperature range	-30°C do +60°C
Device mass	90 kg
EN3 efficiency	III B
Efficiency according to Croatian rulebook	not applicable
Dimensions (diameter/height mm)	318 / 1065
Standard	EN1866
Directives	PED 2014/68/EU

