Help and Support
+385 1 6553 655
info@vatropromet.hr

Fire Hose 52 mm with couplings "Favorit"

1009407

Weaving:

- High tenacity multifilament Polyester yarn
- Warp string double twisted, woven on circular looms and abrasion resistant

Rubber lining:

- UV light and ozone resistant EPDM rubber
- Very good adhesion to the weawing
- Manufactured in a special vulcanizing process

Outer coating:

Favorit is obtainable with a special PU outer coating - giving a resistance against mechanical and chemical damages.

Color: white. Easy to maintain, frost and mildew resistant, light and flexible. Standard hose lenght: 15m.

Technical specifications

Diameter			Weight gr/m	Pressure (Bar)			Max.lenght(m)
Inch	mm	F.M.		Work	Test	Burst	
1	25	D	110	16	24	60	60
1 ½	38	H	190	16	24	60	60
1 ¾	42/45	/	220	16	24	60	60
2	52	C	270	16	24	60	60
2 ½	63/65	/	350	16	24	60	60
2 ¾	70	/	360	16	24	60	60
3	75	B	430	16	24	60	60
4	110	A	625	12	18	35	60

All dimensions of hose are available with cast or forged aluminum couplings banded with wire as well as without the couplings, max. 60m in lenght.



