

## Fire Hose 75 mm with couplings "Herkules"

1009641

The high performance, top quality fire hose for Fire brigades, Refineries, Airports and Docks, Industrial plants, combining resistance to weather, UV-light/ozone, heat, chemicals, oils and abrasion.

### Construction:

- All-in-one extruded fire hose embedding the high tenacity Polyester weaving into a Nitrile/PVC compound

### Major advantage:

- Herkules provides the best rubber-to-textile
- Herkules is unaffected by low/high temperatures (-20°C / +100 °C) and seawater
- No drying required
- Mildew resistant, rot and vermin proof, flexible and very easy to maintain

Standard hose length: 15 m.

## Technical specifications

| Diameter |     |      | Weight gr/m | Pressure (Bar) |      |       | Max.length (m) |
|----------|-----|------|-------------|----------------|------|-------|----------------|
| Inch     | mm  | F.M. |             | Work           | Test | Burst |                |
| 1 ½      | 38  | H    | 360         | 20             | 40   | 60    | 60             |
| 1 ¾      | 45  | /    | 400         | 20             | 40   | 60    | 60             |
| 2        | 52  | C    | 470         | 16             | 32   | 50    | 60             |
| 2 ½      | 63  | /    | 620         | 16             | 32   | 50    | 60             |
| 2 ¾      | 70  | /    | 680         | 16             | 32   | 50    | 60             |
| 3        | 75  | B    | 750         | 16             | 32   | 50    | 60             |
| 4        | 102 | A    | 1060        | 13             | 26   | 40    | 60             |

All dimensions of hose are available with cast or forged aluminum couplings banded with wire as well as without the couplings, max. 60m in length.

