

Fire Hose 75 mm with couplings "Professional - Rekord"

1009411

Certified according to: DIN 14811 / ÖNorm F2105 and other international standards.

The ultimate fire hose for the experienced brigades. A newly developed binding provides this hose with additional abrasion resistance and high flexibility. Approved and certified according to ÖNorm F2105, DIN 14811 and other international standards. Mildew resistant, root and vermin proof, Uv-light/ozone resistant and unaffected by climatic conditions, hot or cold.

Weaving:

- High tenacity Polyester filament yarn woven on circular looms, in a special, reinforcement binding

Rubber lining:

- High quality EPDM rubber lining, UV-light/ozone and ageing resistant
- Very good adhesion to the weaving
- Manufactured in a special vulcanizing process

- Color: White
- Standard hose length: 15 m.

Technical specifications

Diameter			Weight gr/m	Pressure (Bar)			Max.Length(m)
Inch	mm	F.M.		Work	Test	Burst	
1	25	D	190	38	H	60	60
1 ¾	42/45	/	275	16	24	60	60
2	52	C	305	16	24	60	60
2 ½	63/65	/	410	16	24	60	60
2 ¾	70	/	425	16	24	60	60
3	75	B	480	16	24	60	60
4	110	A	690	12	18	35	60

All dimensions of hose are available with cast or forged aluminum couplings banded with wire as well as without the

couplings, max. 60m in lenght.

