

## Fire Membrane Module, 50 bar

100235

Rapid intervention extinguishing kits designed for PickUp vehicles and trailers, equipped with membrane pumps up to 50 Bar with a maximum flow of up to 105 l/min.

### Features:

- High quality components and great replacement part availability.
- Resistant tanks made of 2 mm. AISI-304 stainless steel.
- The best quality/price ratio.
- The weight of the 450 l. kit including the hose is 203.5 kg. (the weight may vary based on the motorization and tank capacity).
- 2 year warranty.

### Water tank:

- Vallfirest tanks feature 2 inner breakwaters to prevent water from moving to the side to ensure vehicle stability.
- The tank has two 1 and 1/2" horizontal holes at the top, one to load water and another for air flow.
- The tank features a 3/4" drain with a plug to empty the tank from the front.
- The tank connects to the pickup bed with 4 anchoring points on a Silemblock system that absorbs load stress and movement.

### Tank dimensions:

- 450 l. T Total w. 1300 mm. | Base w. 1000 mm. | H. 510 mm. | Depth 750 mm.
- 600 l. CS Total w. 1300 mm. | Base w. 1000 mm. | H. 650 mm. | Depth 804 mm.
- 600 l. CD Total w. 1300 mm. | Base w. 1000 mm. | H. 610 mm. | Depth 1050 mm.

### Quick attack winder:

- 70 meter rubber hose up to 80 Bar.
- The winder comes assembled with a connection to the water pump.

