

Firefighter Belt DS, ÖNORM F 4030 type B

1011010

The Type B belt has an integrated stretch lanyard with stitched carabiner in accordance with ÖNORM EN 354 and ÖNORM EN 137, while the stitched carabiner complies with ÖNORM EN 362 and ÖNORM EN 364. The belt is made of 85 mm wide polyester material and 3 mm thick which is fireproof, and a lanyard is made of the same material

The belt has a double D-clip in accordance with ÖNORM F 4030. The belt also includes a safety and lowering plate "EIGHT" made of aluminum, total length 146 mm. The smaller tile hole has a diameter of 26 mm and a larger diameter of 51 mm with a maximum load of 30kN.

Technical specifications

Size 0	waist from 650 mm to 800 mm
Size 1	waist from 700 mm to 1100 mm
Size 2	waist from 950 mm to 1200 mm
Size 3	waist from 1150 mm to 1400 mm
Rastezljiva vezica	750 mm (extensibility +/- 25 mm)

Other features:

- Belt Material: Polyester 85 mm wide, 3 mm thick
- Carabiner Material: Aluminium
- Belt color: Black
- Belt life: Maximum 20 years (with proper use and without damage)
- Tensile life: Maximum 5 years (with proper use and without damage)
- Static harness endurance: 15kN
- Category of personal protective equipment against falls from a height: III. category

Compliance with standards:

- ÖNORM F 4030 - Harness
- ÖNORM EN 358 - Harness
- PPE Safety Guidelines 89/686 / CEE - Belt
- ÖNORM EN 354 - Tensile strap
- ÖNORM EN 137 - Tensile strap
- ÖNORM EN 362 - Carabiner on lanyard
- ÖNORM EN 364 - All metal parts of the product

