



Gas/Petrol Duo Pump SR 20 PC 2

100175

3-stage pump technology:

- Much higher flow/speed in 2nd stage for quicker rescue operations
- Lower flow/speed in 3rd stage for more tool control

Optimal weight / performance ratio:

- Lighter than comparable heavy duty pumps

Soft-grip carrying handle:

- Better grip
- Ergonomic design for improved carrying balance
- Pump easier to carry

Large hydraulic oil capacity:

- Enough oil to operate any two tools at the same time and multiple tools successively, including the biggest rams

Hydraulic oil level indicator on pump:

- Integrated dip stick for quick and easy monitoring of oil level

Technical specifications

Details		
Articlenumber	151.000.856	
Basic specifications		
model	SR 20 PC 2	
equipped with (connector type)	CORE	
max. working pressure	720 / 72 (bar/Mpa)	10443 psi
Performance		
number of stages	3	
capacity oil tank (effective)	4000 cc	135.3 oz

General specifications		
pump type	2 x 3-stage axial pump	
operator type	petrol engine	
number of tool connections	2	
number of tools simultaneously usable	2	
engine	4-stroke - 3.1 HP - 2.3 kW	
Dimensions, weight and temperature		
weight, ready for use	22.9 kg	50.5 lb
dimensions (AxBxC)	455 x 315 x 460 mm	17.9 x 12.4 x 18.1 in
Norms		
EN 13204 classification	MTO	
NFPA 1936 compliant	yes	



