

Hi - Lift First Responder Jack

100361

Firefighter-designed, the First Responder Jack is constructed of steel, cast iron, and high-strength aluminum, and available in 36", 48", and 60" sizes. It offers up to 4660 lbs. of leveraging, lifting, and winching options. No other rescue tool is as easy to use, dependable, visible, and versatile, giving it unlimited potential at a fraction of the cost of other expensive rescue tools.

The First Responder Jack offers the same spreading and ramming options used in extrication as the expensive hydraulic tools at a fraction of the cost. It requires no fuel or power, which makes it ideal for remote access with limited resources, and USAR applications in all types of disasters.

From being first on-scene at a rural accident to deploying RIT for a firefighter down during a structure fire, or searching for victims at the largest of incidents, there is no tool in the fires service that offers more versatility than the First Responder Jack. Removable top clamp-clevis attachment is rated to the full capacity of the jack for winching, clamping and spreading. Durable powder-coated bright yellow main components with fire red actuating pieces.

Safe Use Information including rated load details and operating instructions. Aggressive 36 sq. inch base provides a safe and effective platform, while offering a wide array of rescue options that encompass; cribbing, chains, straps, and has a 360 degree pinnable rotation platform. Luminescent features for use in IDLH and low light atmospheres.

Only Hi-Lift® First Responder Jacks are designed to be used for advanced rescue and extrication maneuvers. Standard model Hi-Lift® Jacks are designed for basic lifting, winching, and clamping only.

Technical specifications

Size	Responder Jack 36" (91 cm)	Responder Jack 48" (122 cm)	Responder Jack 60" (152 cm)
Min. Lift Height	6.75" (17.14 cm)	6.75" (17.14 cm)	6.75" (17.14 cm)
Max. Lift Height	27" (68.58 cm)	38.63" (98.12 cm)	49.75" (126.37 cm)
Overall Height	41" (104.14 cm)	50.75" (128.91 cm)	61.75" (156.85 cm)
Width	5" (12.7 cm)	5" (12.7 cm)	5" (12.7 cm)
Depth	9.63" (24.46 cm)	9.63" (24.46 cm)	9.63" (24.46 cm)
Rated Load (RL)	4660 lbs (2113 kg)	4660 lbs (2113 kg)	4660 lbs (2113 kg)
RL on upper 12"/30.5 cm	-	-	-2660 lbs (1206 kg)
Tested Load (TL)	7000 lbs (3175 kg)	7000 lbs (3175 kg)	7000 lbs (3175 kg)
TL on upper 12"/30.5 cm	-	-	4000 lbs (1814 kg)

Winching capacity	7000 lbs (3175 kg)	7000 lbs (3175 kg)	7000 lbs (3175 kg)
Clamping capacity	7000 lbs (3175 kg)	7000 lbs (3175 kg)	7000 lbs (3175 kg)
Weight	27 lbs (12.25 kg)	30.2 lbs (13.70 kg)	33.3 lbs (15.10 kg)

