

## Large flow ventilator EASY 2000 on Skid - 220,000 m<sup>3</sup>/h

EASY-2000-SKID

EASY 2000 large-flow ventilator is the best in its class! With a flow rate of 220,000 m<sup>3</sup>/h, it allows smoke removal and cooling of large volumes (covered/closed parking lots, warehouses, production lines, medium/high-rise buildings, exhibition halls, etc.).

Alone, it is an effective response to ventilate large volumes. Several, they offer flexibility of action because they can be used simultaneously to optimise the blowing power. They can also be distributed at various strategic points of a city.

### Product Features

#### Large flow

EASY 2000 large-flow ventilator is the best in its class. With a flow rate of 220,000 m<sup>3</sup>/h, it allows smoke removal and cooling of large volumes (covered/closed parking lots, warehouses, production lines, exhibition halls, etc.).

#### Easy to operate by one person

Thanks to its extremely low weight (less than 180 kg), EASY 2000 Large-Flow ventilator is very easy to operate by one person.

#### Adaptable to all types of vehicles

EASY 2000 large-flow ventilator is available in two versions to meet different configurations:

- On Skid: can be used on a forklift truck, trolley, tracked vehicle or on a vehicle bed (pick-up type)
- Trailer-mounted

#### Many options available

EASY 2000 large-flow ventilator can be equipped with many options such as 600 mm or 1200 mm lifting table, LED headlight, exhaust extension, blowing or suction ducts, and manual 360° rotation system.

### Technical specifications

- Open air flow: 220,000 m<sup>3</sup>/h
- Weight: Without elevation: 158 kg / Elevation 600mm: 299 kg / Elevation 1200mm: 344 kg
- Dimensions W x H x D: Without elevation: 1205 x 1250 x 1060mm / Elevation 600mm: 1293 x 1510 x 1060mm / Elevation 1200mm: 1293 x 1645 x 1060 mm
- Propeller diameter: 885 mm
- Support: Skid on red epoxy-painted steel chassis adaptable on the platform of a trailer, pick-up, truck, etc. (all delivered on pallet)
- Engine control panel: yes

- 
- Wired remote control: yes
  - Mistng system: For water or water+additives – 260 l/min @ 7 bar
  - Engine: HONDA GX630.
  - Engine power: 20.8 HP
  - Tank: 18 litres
  - Fuel: Unleaded petrol SP95
  - Autonomy: 3:05 h
  - Oil: Engine oil: 5W-30 synthetic API SJ or later (CASTROL MAGNATEC). Hydraulic oil for lifting option: CASTROL SAF XJ 75-140
  - Battery: 12V / 44 Ah battery to power the electrical equipment
  - Noise level: 93.9 dB at 7 m
  - Ventilation type: PPV
  - Application: Ventilating underground parking lots, industrial sites, warehouses, tunnels, etc.



