

Large-flow ventilator EASY 2000 trailer-mounted - 220,000 m³/h

EASY-2000-TRAILER

EASY 2000 large-flow ventilator is the best in its class! With a flow rate of 220,000 m³/h, it allows smoke removal and cooling of large volumes (covered/closed parking lots, warehouses, production lines, medium/high-rise buildings, exhibition halls, etc.).

Alone, it is an effective response to ventilate large volumes.

Several, they offer flexibility of action because they can be used simultaneously to optimise the blowing power. They can also be distributed at various strategic points of a city.

Product Features

Large flow

EASY 2000 large-flow ventilator is the best in its class. With a flow rate of 220,000 m³/h, it allows smoke removal and cooling of large volumes (covered/closed parking lots, warehouses, production lines, exhibition halls, etc.).

Easy to operate by one person

Thanks to its extremely low weight (less than 325 kg), EASY 2000 LFV (Large-Flow Ventilator) is very easy to operate by one person.

Adaptable to all types of vehicles

EASY 2000 large-flow ventilator is available in two versions to meet different configurations:

- On Skid: can be used on a forklift truck, trolley, tracked vehicle or on a vehicle bed (pick-up type)
- Trailer-mounted

Many options available

EASY 2000 large-flow ventilator can be equipped with many options such as 600 mm or 1200 mm lifting table, LED headlight, exhaust extension, blowing or suction ducts, etc.

Technical specifications

- Open air flow: 220,000 m³/h
- Weight: Without elevation: 301 kg / Elevation 600mm: 402 kg / Elevation 1200mm: 447 kg
- Dimensions W x H x D: Without elevation: 2800 x 1715 x 1430mm / Elevation 600mm: 2800 x 1915 x 1430mm / Elevation 1200mm: 2800 x 2050 x 1430 mm
- Propeller diameter: 885 mm
- Support: Single-axle trailer with brakes, towball and sealed enclosure
- Engine control panel: yes
- Wired remote control: yes

- Mistig system: For water or water+additives – 260 l/min @ 7 bar
- Engine: HONDA GX630.
- Engine power: 20.8 HP
- Tank: 18 litres
- Fuel: Unleaded petrol SP95
- Autonomy: 3:05 h
- Oil: Engine oil: 5W-30 synthetic API SJ or later (CASTROL MAGNATEC), Hydraulic oil for lifting option: CASTROL SAF XJ 75-140
- Battery: 12V / 44 Ah battery to power the electrical equipment
- Noise level: 93.9 dB at 7 m
- Ventilation type: PPV
- Application: Ventilating underground parking lots, industrial sites, warehouses, tunnels, etc.

