

LED Beacon B14, Magnetic

100241

Features:

- Multi-Voltage Input 12 - 24 VDC.
- LEDs rated to 100,000 hours of operation.
- Non-volatile memory recalls last flash pattern used at power up.
- Multiple units are synchronizable and can flash simultaneously or alternately.
- Reverse polarity protection.
- Weatherproof and vibration resistant design for external or internal use.

Technical specifications

- Compliance: ECE R65(TA1; TB1; TR1); ECE-R10; SAE J845; CA13; IPX5
- Operating Voltage: 12 - 24 VDC
- Warning Patterns: 14 Flash Patterns
- LED Elements: 3W LED x 10 pcs Avg.
- Current: 1.7A @12.8VDC | 0.88A @24VDC (varies with flash pattern)
- Avg. Power: 21 W (varies with flash pattern)
- Max. Current: 3.3A @12.8VDC | 1.75A @24VDC
- Max. Power: 42 W

Wires:

Magnetic Mount:

- Single button cigar-plug: 300cm
- European cigar-plug: 250cm

Permanent Mount:

- Red-Vcc : 40cm /15.74in (20AWG)
- Black-GND: 40cm /15.74in (20AWG)
- Yellow-Flash Patterns & Sync: 40cm /15.74in (20AWG)
- White-Phase: 40cm /15.74in (20AWG)

- Recommended Fuse: 5A
- Multi-Unit Synchronization: Up to 4 units

-
- Storage Temperature: -40°C to +75°C
 - Operating Temperature: -30°C to +65°C
 - LED Colour: Red, Blue, or Amber
 - Lens Colour: Red, Blue, or Amber
 - Warranty: 5 Years

