

LED Beacon B16, Point Mount

100242

Features:

- Multi-Voltage Input 12 - 24 VDC.
- LEDs rated to 100,000 hours of operation.
- Non-volatile memory recalls last flash pattern used at power up.
- Multiple units are synchronizable and can flash simultaneously or alternately.
- Reverse polarity protection.
- Weatherproof and vibration resistant design for external or internal use.

Technical specifications

- Meets: ECE-R65, ECE-R10, SAE
- Operating Voltage: 12~24VDC
- Warning Patterns: 11 Flash Patterns
- Bulb: 3W LED x 8 pcs
- Avg. Current: 1.2A @12.8VDC / 0.7A @24VDC (varies with flash pattern)
- Avg. Power: 15Watts (varies with flash pattern)
- Max. Current: 2.4A @12.8VDC / 1.3A @24VDC
- Max. Power: 30Watts

Wires:

Magnetic Mount:

- Single button cigar-plug: 300cm
- European cigar-plug: 250cm

Permanent Mount:

- Red-Vcc : 40cm (20AWG)
- Black-GND: 40cm (20AWG)
- Yellow-Flash Patterns & Sync: 40cm (20AWG)
- White-Phase: 40cm (20AWG)

- Fuse Recommended: 5
- Multi-Unit Synchronization: Over 15

-
- Storage Temperature: -40°C to +75°C
 - Operating Temperature: -30°C to +65°C

