

LED Lighthead Power LED 4

1006339

- High-Intensity 1W LED x 4
- Multi-Voltage Input 11~30VDC
- Built-in 19 Selectable Flash Patterns
- LEDs rated to 100,000 hours of operation.
- Non-volatile memory recalls last flash pattern used at power up.
- Multiple units are synchronizable and can flash simultaneously or alternately.
- Reverse polarity protection.
- Weatherproof and vibration resistant design for external or internal use.
- Aluminum base for heat dissipation.

Technical specifications

• Meets: SAE, Title XIII, e13, E13

• Bulb: 1W LED x 4pcs

• Warning Patterns: 19 Flash Patterns

• Operating Voltage: 11~30VDC

Avg. Current: 0.28A@12.8VDC 0.15A@24VDC

• (varies with flash pattern)

Avg. Power: 3.6 Watts (varies with flash pattern)
Max. Current: 0.56A@12.8VDC 0.3A@24VDC

Max. Power: 7.2 Watts

• Wires: Red-Vcc: 20cm (20AWG)

• Black-GND: 20cm (20AWG)

Yellow-Flash Patterns & Sync: 20cm (20AWG)

• White-Phase: 20cm (20AWG)

• Fuse Recommend: 3A

Multi-Unit Synchronization: Over 15
Storage Temperature: -40°C to +75°C
Operating Temperature: -30°C to +65°C

• Available in: Blue

