

LED Lighthead XT6

100250

- New Generation Xtreme optic for wide angle visual and classic aesthetics.
- SAE and ECE R65 certified high power output.
- ECE R10 EMC Compliance.
- 0.39" (10mm) Super low-profile thickness.
- Long life LEDs rated to 100,000 hours of operation.
- Non-volatile memory recalls last flash pattern used at power up.
- Multi-units synchronization in simultaneous or alternating flash.
- Reverse polarity protection.
- Weatherproof and vibration resistant design for internal or external use.
- Solid aluminum base for efficient heat dissipation.

Technical specifications

Meets: ECE R65 (XA1, XB1), ECE R10, SAE J595 Class 1, CA Title 13 (R, B), IPX8

Bulb: High-power LED x 6pcs

Warning Patterns: 16 Flash Patterns

Operating Voltage: 12~24VDC

Avg. Current: 0.44A @12VDC / 0.22A @24VDC

(varies with flash pattern)

Avg. Power: 5.3 Watts (varies with flash pattern)

Max. Current: 0.88A @12VDC / 0.44A @24VDC

Max. Power: 10.6 Watts

Wires: Red-Vcc : 25cm (20AWG)

Black-GND : 25cm (20AWG)

Yellow-Sync & Functions : 25cm (20AWG)

Fuse Recommended: 1A

Available in: Blue

