

Lifting Bag HLB 16

100185

High-pressure lifting bag, 12 bar / 174 psi system. Designed for maximum safety and control when lifting heavy objects. Offers 50% more lifting capacity: get more power out of your lifting bag or use a smaller and lighter model to get the job done.

High-pressure lifting bag, 12 bar / 174 psi system. Designed for maximum safety and control when lifting heavy objects. Offers 50% more lifting capacity: get more power out of your lifting bag or use a smaller and lighter model to get the job done.

Clear indication of safety warnings, technical specifications and lifting height:

- To help you work safer and easier

Center markings on all sides:

- To help you position a smaller bag onto a larger model

Non-slip surface with interlocking profile:

- To maximize the contact area and stability of inflated lifting bags

Reflective markings:

- For optimal visibility in the dark

Compliant with relevant safety standards:

- Meets EN 13731 and other legislative requirements

Integrated carrying handle with capacity indication:

- For easy carrying
- Quickly pull the right lifting bag from storage

Standard equipped with slider pads:

- For easy insertion underneath an object

Technical specifications

Details		
Articlenumber	350.321.026	
Basic specifications		
model	HLB 16	
max. working pressure	12 / 1.2 (bar/Mpa)	174 psi
Performance		
max. lifting capacity	155 / 15.8 (kN/t)	34845 lbf
max. inflation height	236 mm	9.3 in
thickness incl. profile	25 mm	1 in
max. lifting capacity (12 bar/174 psi)	155 / 15.8 (kN/t)	34845 lbf
max. lifting capacity (8 bar/116 psi)	103 / 10.5 (kN/t)	23155 lbf
General specifications		
material	reinforced with 3 aramide inlays	
air content (8 bar/116 psi)		2.5 cu ft
Dimensions, weight and temperature		
weight, ready for use	4.5 kg	9.9 lb
dimensions (AxBxC)	467 x 390 x 25 mm	18.4 x 15.4 x 1 in
Norms		
EN-13731	Yes	



