

Lifting Bag HLB 2

100181

High-pressure lifting bag, 12 bar / 174 psi system. Designed for maximum safety and control when lifting heavy objects. Offers 50% more lifting capacity: get more power out of your lifting bag or use a smaller and lighter model to get the job done.

Clear indication of safety warnings, technical specifications and lifting height:

- To help you work safer and easier

Center markings on all sides:

- To help you position a smaller bag onto a larger model

Non-slip surface with interlocking profile:

- To maximize the contact area and stability of inflated lifting bags

Reflective markings:

- For optimal visibility in the dark

Compliant with relevant safety standards:

- Meets EN 13731 and other legislative requirements

Technical specifications

Details		
Articlenumber	350.321.021	
Basic specifications		
model	HLB 2	
max. working pressure	12 / 1.2 (bar/Mpa)	174 psi
Performance		
max. lifting capacity	21 / 2.1 (kN/t)	4721 lbf
max. inflation height	94 mm	3.7 in
thickness incl. profile	22 mm	0.9 in

max. lifting capacity (12 bar/174 psi)	21 / 2.1 (kN/t)	4721 lbf
max. lifting capacity (8 bar/116 psi)	14 / 1.4 (kN/t)	3147 lbf
General specifications		
material	reinforced with 3 aramide inlays	
air content (8 bar/116 psi)		0.2 cu ft
Dimensions, weight and temperature		
weight, ready for use	0.7 kg	1.5 lb
dimensions (AxBxC)	200 x 160 x 22 mm	7.9 x 6.3 x 0.9 in
Norms		
EN-13731	Yes	



