

MGT Docking Station

100413

Bump test and calibration are the key features to ensure the safety of devices and users.

The MGT Docking Station v2. MGT docking station version II provides bump testing, event management and calibration from a simple to use multi-unit station and gives fleet or safety managers the ability to update configurations on large fleets. It also maintains the all important event logs that demonstrate users are working within company requirements.

Technical specifications

Size	52.5 x 43.7 x 21.3cm(20.66" x 17.20" x 8.40")
Weight (Without gas cylinder)	11.0kg
Operating Temperature	41 to +104°F (5 to +40°C)
Warranty	2 years
Battery Type	Rechargeable Lithium Ion
Battery Life	1,000 Bump Tests
LEDs	6 Blue LEDs for each unit(unit x 4), 3-color LED for power, Switch Back Light LED (Yellow, Green)
Memory	USB 8GB Standard
Log Capacity	Approximately Up to 5 million tests(8GB, removable USB memory)
Tests Performed	Bump Test and Calibration
Information Stored	Bump/Cal Logs, Individual Monitor Event Logs, Firmware and Unit Configurations
Gases Available	LEL, CO, H ₂ S and O ₂
Unit Compatibility	Works with SP-MGT(N, P)
Calibration Gas	Compatible with 58L & 116L cylinders
Interface	Ethernet RJ-45(TCP/IP), 10Mb/s
Charging Adaptor	DC12.0V, 3A/h

