

Power Generator ESE 1408 DBG ES DIN Super Silent Plus

100277

Advantages:

- Fitted according to DIN 14685-1
- Comprehensive functions, safe and simple operation
- DUPLEX current quality without compromise
- Multifunctional control display E-MCS 4.0 - a clear system
- A large tank for long operation - with re-fuelling
- Emergency start function over the recoil starter
- Special equipment and accessories, available for many requirements

Equipment features:

- Insulation monitoring - without shut-off
 - 3-way fuel cock for external refuelling
 - Multifunction control display E-MCS 4.0
 - Fuel level indicator over the E-MCS 4.0
 - Lack of oil automatic switch-off
 - Alternator overload protection
 - Starter battery 12 V/20 A
 - Folding handles
 - Vehicle tool kit
 - ECOtronic
-
- LED instrument panel illumination

Technical specifications

Alternator type	Duplex
Continuous Power 3~ [kVA/kW]	13.9/11.2
Continuous Power 1~ [kVA/kW]	7.5/6.7
Nominal voltage [V]	400/230
Nominal Current [A]	20,1/32,6
Power factor cos (phi)	0,8
Frequency [Hz]	50

Protection Class [IP]	54
Engine	
Engine Type	B&S Vanguard 23 HP
Design	2-Zyl. 4-Takt OHV
Displacement [ccm]	627
Output 3000 rpm	15,0
CO ₂ emissions [g / kWh]	22
CO ₂ test procedure	22
Fuel	Benzin
Fuel tank capacity [l]	12
Fuel consumption @ 75% PRP [L/h]	5,6
Running time @ 75% PRP	2,1
Starting system	Elektrostart
Sound power level LWA [db(A)]	96
Weight in kg ca.	144
Dimensions L x W x H [mm]	820 x 440 x 580
Shockproof sockets	3 x 230V 16A 2 x 400V CEE 16A

