

Power Generator ESE 3000i

3007151

-46% 2187,50 kn
1187.50 kn

Advantages at a glance:

- Inverter technology
- High-quality current
- Compact and sildent
- Easy handling

Equipment features:

- Lack of oil automatic switch-off
- Alternator overload protection
- Variable speed constant frequency (VSCF)
- Connection for a 12 V battery charge
- Parallel running
- USB connection
- Extendable hand grip
- Transport wheels

Possible applications	230 V
Electronic consumers up to	3000 W
Electric tools up to	2750 W
Garden equipment up to	2350 W

Technical specifications

Alternator type	synchron
Max. Output 1~ [kVA/kW]	3.3/3.3
Continuous Power 1~ [kVA/kW]	3.0/3.0
Nominal voltage [V]	230
Nominal Current [A]	13,0
Power factor cos (phi)	1
Frequency [Hz]	50
Protection Class [IP]	23
Engine Type	Endress 175/E

Design	1-Zylinder 4-Takt OHV
Displacement [ccm]	171
Output 3000 rpm	4,2
CO2 emissions [g / kWh]	22
CO ₂ test procedure	22
Fuel	Petrol
Fuel tank capacity [l]	46,8
Fuel consumption @ 75% PRP [L/h]	1,36
Running time @ 75% PRP	5
Starting system	E-start, uključujući bateriju
Sound power level LWA [db(A)]	93
Sound pressure level LPA (7 m) [db(A)]	68
Weight in kg ca.	41
Dimensions L x W x H [mm]	588 x 442 x 452
Shockproof sockets	1 x 230 V / 16 A 1x 12V / 8,3 A 1x USB 5V / 2,1 A



