

Power Generator ESE 304 HG DIN

100264

Advantages:

- Fitted according to DIN 14685-2
- Comprehensive functions, safe and simple operation
- DUPLEX current quality without compromise
- Special equipment and accessories, available for many requirements

Equipment features:

- Insulation monitoring – without shut-off
- 3-way fuel cock for external refuelling
- Fuel indicator
- Lack of oil automatic switch-off
- Alternator overload protection
- Folding handles
- Vehicle tool kit

Technical specifications

Alternator type	Duplex
Continuous Power 1~ [kVA/kW]	3.0/2.4
Nominal voltage [V]	230
Nominal Current [A]	13,0
Power factor cos (phi)	0,9
Frequency [Hz]	50
Protection Class [IP]	54
Engine	
Engine Type	Honda GX200
Design	1-Zyl. 4-Takt OHV
Displacement [ccm]	196
Output 3000 rpm	4,1
CO2 emissions [g / kWh]	22
CO2 test procedure	22
Fuel	Petrol

Fuel tank capacity [l]	3,1
Fuel consumption @ 75% PRP [L/h]	1,5
Running time @ 75% PRP	2,1
Starting system	Reversierstart
Sound power level LWA [db(A)]	95
Weight in kg ca.	54
Dimensions L x W x H [mm]	550 x 440 x 400
Shockproof sockets	2 x 230V 16A

