Help and Support
+385 1 6553 655
info@vatropromet.hr

Power Generator ESE 604 DHG DIN

100265

Advantages:

- Fitted according to DIN 14685-1
- Comprehensive functions, safe and simple operation
- DUPLEX current quality without compromise
- Multifunctional control display E-MCS 4.0 - a clear system
- Special equipment and accessories, available for many requirements

Equipment features:

- Insulation monitoring – without shut-off
- 3-way fuel cock for external refuelling
- Multifunction control display E-MCS 4.0
- Fuel level indicator over the E-MCS 4.0
- Lack of oil automatic switch-off
- Alternator overload protection
- Folding handles
- Vehicle tool kit

Technical specifications

Alternator type	Duplex
Continuous Power 3~ [kVA/kW]	6.0/4.8
Continuous Power 1~ [kVA/kW]	4.0/3.6
Nominal voltage [V]	400/230
Nominal Current [A]	8.7/17.4
Power factor cos (phi)	0,8
Frequency [Hz]	50
Protection Class [IP]	54
Engine	
Engine Type	HONDA GX390 / 11 HP
Design	1-Zylinder 4-Takt OHV
Displacement [ccm]	389
Output 3000 rpm	6,4

CO2 emissions [g / kWh]	22
CO2 test procedure	22
Fuel	Petrol
Fuel tank capacity [l]	6,5
Fuel consumption @ 75% PRP [L/h]	2,1
Running time @ 75% PRP	3,1
Starting system	Reversierstarter
Sound power level LWA [db(A)]	97
Sound pressure level LPA (7 m) [db(A)]	72
Weight in kg ca.	95
Dimensions L x W x H [mm]	700 x 440 x 580
Shockproof sockets	3 x 230V 16A 1x CEE 400V 16A

