

Power Generator ESE 606 DHS-GT, Non EU

100130

- Large tank for long running times
- Alternator overload protection
- Tank level indicator
- 4 in 1 display = V / Hz / h / oil deficit
- Folding handles
- AVR regulation
- Wheelset as standard

Electric tools up to	4900 W	3200 W
Gardening or construction equipment up to	3300 W	2200 W
Inverter welding equipment up to a dia. of 2.50 mm		
Compressors or pumps up to	2500 W	1600 W
Possible applications	400 V	230 V

Technical specifications

Alternator type	synchron
Max. Output 3~ [kVA/kW]	7.5/6.0
Max. Output 1~ [kVA/kW]	4.2/4.2
Continuous Power 3~ [kVA/kW]	7.0/5.6
Continuous Power 1~ [kVA/kW]	3.7/3.7
Nominal voltage [V]	400/230
Nominal Current [A]	10.8/16
Power factor cos (phi)	0,8/1,0
Frequency [Hz]	50
Protection Class [IP]	23
Engine	
Engine Type	HONDA GX390 / 11 HP
Design	1-Zylinder 4-Takt OHV
Displacement [ccm]	389
Output 3000 rpm	6,4

CO2 emissions [g / kWh]	22
CO2 test procedure	22
Fuel	Benzin
Fuel tank capacity [l]	30
Fuel consumption @ 75% PRP [L/h]	2,1
Running time @ 75% PRP	14,3
Starting system	Reversierstart
Sound power level LWA [db(A)]	97
Sound pressure level LPA (7 m) [db(A)]	72
Weight in kg ca.	90
Dimensions L x W x H [mm]	786 x 570 x 600
Shockproof sockets	1 x 230V 16A 1 x CEE 400V 16A



