

Power Generator ESE 606 DHS-GT

100134

Equipment features:

- Lack of oil automatic switch-off
- Alternator overload protection
- HONDA + Briggs & Stratton OHV engines
- Large tank for long running times
- Compound regulated high performance generators for 400 V

Electric tools up to	5500 W	3100 W
Electric tools up to	3700 W	2100
Garden equipment up to	2800 W	1600
Inverter welding equipment up to a dia. of 3.25 mm		
Possible applications	400 V	230 V

Technical specifications

Alternator type	synchron
Max. Output 3~ [kVA/kW]	8,3/6,6
Max. Output 1~ [kVA/kW]	4.9/4.4
Continuous Power 3~ [kVA/kW]	7.0/5.6
Continuous Power 1~ [kVA/kW]	3.5/3.2
Nominal voltage [V]	400/230
Nominal Current [A]	10,1/15,2
Power factor cos (phi)	0,8/0,9
Frequency [Hz]	50
Protection Class [IP]	23
Engine	
Engine Type	HONDA GX390 / 11 HP
Design	1-Zylinder 4-Takt OHV
Displacement [ccm]	389
Output 3000 rpm	6,4
CO2 emissions [g / kWh]	22

CO2 test procedure	22
Fuel	Benzin
Fuel tank capacity [l]	30
Fuel consumption @ 75% PRP [L/h]	2,1
Running time @ 75% PRP	14,3
Starting system	Reversierstart
Sound power level LWA [db(A)]	97
Sound pressure level LPA (7 m) [db(A)]	72
Weight in kg ca.	81
Dimensions L x W x H [mm]	800 x 538 x 576
Shockproof sockets	1 x 230 V/16 A 1 x CEE 230 V/16 A 1 x CEE 400 V/16 A

