

Power Generator ESE 606 HS-GT

100133

Equipment features:

- Lack of oil automatic switch-off
- Alternator overload protection
- HONDA + Briggs & Stratton OHV engines
- Large tank for long running times
- Compound regulated high performance generators for 400 V

Electric tools up to	5400 W
Gardening or construction equipment up to	3600 W
Compressors or pumps up to	2800 W
Possible applications	230 V

Technical specifications

Alternator type	synchron
Max. Output 1~ [kVA/kW]	7.2/6.4
Continuous Power 1~ [kVA/kW]	6.0/5.5
Nominal voltage [V]	230
Nominal Current [A]	26,1
Power factor cos (phi)	0,9
Frequency [Hz]	50
Protection Class [IP]	23
Engine	
Engine Type	HONDA GX390 / 11 HP
Design	1-Zylinder 4-Takt OHV
Displacement [ccm]	389
Output 3000 rpm	6,4
CO2 emissions [g / kWh]	22
CO2 test procedure	22
Fuel	Benzin
Fuel tank capacity [l]	30
Fuel consumption @ 75% PRP [L/h]	2,1

Running time @ 75% PRP	14,3
Starting system	Reversierstart
Sound power level LWA [db(A)]	97
Sound pressure level LPA (7 m) [db(A)]	72
Weight in kg ca.	77
Dimensions L x W x H [mm]	800 x 538 x 576
Shockproof sockets	1 x 230 V/16 A 1 x CEE 230 V/32 A

