

Power Generator ESE 954 DBG DIN

100267

Advantages:

- Fitted according to DIN 14685-1
- Comprehensive functions, safe and simple operation
- DUPLEX current quality without compromise
- Multifunctional control display E-MCS 4.0 - a clear system
- Special equipment and accessories, available for many requirements

Equipment features:

- Insulation monitoring - without shut-off
- 3-way fuel cock for external refuelling
- Multifunction control display E-MCS 4.0
- Fuel level indicator over the E-MCS 4.0
- Lack of oil automatic switch-off
- Alternator overload protection
- Folding handles
- Vehicle tool kit

Technical specifications

Alternator type	Duplex
Continuous Power 3~ [kVA/kW]	9.0/7.2
Continuous Power 1~ [kVA/kW]	6.0/5.4
Nominal voltage [V]	400/230
Nominal Current [A]	13/26.1
Power factor cos (phi)	0,8
Frequency [Hz]	50
Protection Class [IP]	54
Engine	
Engine Type	B&S Vanguard 16 HP
Design	2-Zyl. 4-Takt OHV
Displacement [ccm]	479
Output 3000 rpm	9,5

CO2 emissions [g / kWh]	22
CO2 test procedure	22
Fuel	Petrol
Fuel tank capacity [l]	8,5
Fuel consumption @ 75% PRP [L/h]	2,4
Running time @ 75% PRP	3,5
Starting system	Reversierstart
Sound power level LWA [db(A)]	97
Weight in kg ca.	110
Dimensions L x W x H [mm]	700 x 440 x 580
Shockproof sockets	3 x 230V 16A 1 x 400V CEE 16A



Ilustracija
Illustration similar