

Ram RA 5313 CL

100167

Decreased weight:

- Lighter than ever, thanks to new materials, component integration and smart design. Very easy to carry and handle, reducing physical strain.

Built-in Speed Valve:

- When unloaded, the plunger extends quickly to the desired distance to speed up positioning of your ram

Rotating cross heads with improved, precision cast profile:

- Easy positioning and perfect grip in any situation

New control handle:

- Improved ergonomic design, offering better grip for optimal tool control

Technical specifications

Details		
Articlenumber	150.032.120	
Basic specifications		
model	RA 5313 CL	
equipped with (connector type)	CORE	
max. working pressure	720 / 72 (bar/Mpa)	10443 psi
Performance		
spreading force over full stroke	100 / 10.2 (kN/t)	22481 lbf
spreading stroke	250 mm	9.8 in
retracted length	415 mm	16.3 in
extended length	665 mm	26.2 in
directives	2006/42/EG	
General specifications		
number of plungers	1	
Dimensions, weight and temperature		

weight, ready for use	7.8 kg	17.2 lb
dimensions (AxBxC)	256 x 100 x 415 mm	10.1 x 3.9 x 16.3 in
Norms		
EN 13204 classification	R100/250-7.8	
NFPA 1936 compliant	yes	
EN 13204 compliant	yes	
NFPA 1936, HSF	100 / 10.2 (kN/t)	22481 lbf
NFPA 1936, LSF	100 / 10.2 (kN/t)	22481 lbf

