

Ram RA 5332

100170

Optimal performance to weight ratio:

- High spreading force compared to tool weight

Built-in Speed Valve:

- When unloaded, the plunger extends quickly to the desired distance, to speed up positioning of your ram

Rotating cross heads with improved, precision cast profile:

- Easy positioning and perfect grip in any situation

Ergonomic carrying handle:

- New handle design for easy carrying
- Mounted parallel to tool to limit dimensions

Integrated LED lighting:

- Illumination of both the plunger and the base side of the ram (4 LED lights in total)
- You can start right away, both during the day and at night, without working in your own shadow

New control handle:

- Improved ergonomic design, offering better grip for optimal tool control

Protective strips on housing:

- To protect the tool from damage when putting it on the ground

Snap-lock system for accessories:

- Changing of accessories within seconds, without the use of tools

Technical specifications

| Details | |
|---------|--|
| | |

| | | |
|------------------------------------|--------------------|--------------------|
| Articlenumber | 151.000.390 | |
| Basic specifications | | |
| model | RA 5332 | |
| equipped with (connector type) | CORE | |
| max. working pressure | 720 / 72 (bar/Mpa) | 10443 psi |
| Performance | | |
| spreading force over full stroke | 150 / 15.3 (kN/t) | 33721 lbf |
| spreading / pulling stroke | 680 mm | 26.8 in |
| retracted length | 950 mm | 37.4 in |
| extended length | 1630 mm | 64.2 in |
| pulling force over full stroke | 28 / 2.9 (kN/t) | |
| General specifications | | |
| number of plungers | 2 | |
| Dimensions, weight and temperature | | |
| weight, ready for use | 19.3 kg | 42.5 lb |
| dimensions (AxBxC) | 280 x 105 x 950 mm | 11 x 4.1 x 37.4 in |
| Norms | | |
| EN 13204 classification | R150/680-19.3 | |
| NFPA 1936 compliant | yes | |
| EN 13204 compliant | yes | |
| NFPA 1936, HPF | 28 / 2.9 (kN/t) | 6295 lbf |
| NFPA 1936, HSF | 150 / 15.3 (kN/t) | 33721 lbf |
| NFPA 1936, LPF | 28 / 2.9 (kN/t) | 6295 lbf |
| NFPA 1936, LSF | 150 / 15.3 (kN/t) | 33721 lbf |



