

Rechargeable Flashlight Nightstick NSR-9514XL

Kat. br. 017398803045

The rechargeable aircraft-grade aluminum LED flashlight, offers 3 microprocessor-controlled brightness modes as well as a strobe function. This light has an impressive runtime of 6.5 hours in full brightness mode.

The 850 lumen output in combination with the high efficiency deep parabolic reflector design throws a usable beam of light 325 meters. Designed with dual buttons, one located on the waterproof body of the light, and the other in the tail cap. Meets requirements of NFPA-1971-8.6 (2013).

Features:

- LED technology
- Momentary or constant-on plus 3 brightness levels & strobe
- Sharp focused beam
- Aircraft-grade 6061-T6 aluminum housing, tail-cap & bezel w/Type III hard anodized finish
- Non-slip grip
- Body & tail switch
- IP-X7 Waterproof
- Impact & chemical resistant
- Serialized for personal identification
- Rechargeable Lithium-ion battery (included)

Technical specifications

- Multi-Function: Yes
- High Lumens: 850
- Medium Lumens: 200
- Low Lumens: 50
- High Beam Distance (m): 325
- Medium Beam Distance (m): 166
- Low Beam Distance (m): 85
- High Candela: 26,280
- Medium Candela: 6,880
- Low Candela: 450
- Drop Rating: 2 m
- Water Rating: IP-X7 Waterproof
- High Runtime (h): 6.5
- Medium Runtime (h): 9
- Low Runtime (h): 50
- Strobe: Yes
- Strobe Runtime (h): 5.5

-
- Charge Time (h): 4
 - Switch Function: Single Body Switch & Single Tail Switch (Tandom Functionality) - Momentary or Constant-on Flashlight, High, Medium and Low-Brightness Flashlight, Strobe
 - Light Source: LED
 - Serialized: Y
 - Case Material: 6061-T6 Aluminum
 - Body Color: Black
 - Quantity of Batteries: 1
 - Power Source: Li-ion Rechargeable
 - Package Contents: Light, Anti-roll Ring, Rechargeable Lithium-ion Battery, AC Power Supply, DC Power Supply and Charger
 - US Patent(s) : 9713217
 - Warranty: Limited Lifetime Warranty

Dimensions:

- Length: 8.9 in (226 mm)
- Weight: 10.1 oz (286 g)
- Handle Diameter: 1.2 in (30 mm)
- Head Diameter: 1.6 in (41 mm)



