

Respiratory Face mask S-H

100033

The S-H mask is equipped with an ambient air hatch enabling the user to have the mask fully donned and still breathe ambient air to save the compressed air in the cylinder. With a very simple operation, a push on the hatch cover, the air from the cylinder is activated.

With this solution the user is always sure to have a perfect seal. The risk for improper mounting of the breathing valve while wearing the mask is eliminated when it is kept correctly connected at all times. In addition, the breathing valve is always protected and never exposed to dirt, contamination and mechanical exposure.

The breathing valve has a positive lock to the mask providing a secure connection at all times. After preparing and connecting the mask to the breathing valve there is no risk for unintentional disconnection.

The mask and breathing valve design is very compact with no protruding parts which gives unrestricted visibility and reduce the risk of snagging and mechanical damage. The silent operation of the mask gives minimal noise interference and excellent communication possibilities.

- Secure positive lock connection of the breathing valve to the face mask
- Demand controlled and activated from inner mask providing excellent breathing performance
- Open ambient air hatch is indicated with a highly visible indicator arm
- Prepared and compatible with voice communication systems, "Heads-Up Display" and spectacle kit
- Ergonomic head harness with easily operated buckles

The standard version is made from natural rubber and has a 5-point head harness. This version is available in the three different sizes Standard size, Small size (S) and X-large size (XL).

The silicone version is available in Standard size.

There is also a version compatible with helmet adapters with a 4-point head harness and a top strap. This version is available in Standard size. When ordering this mask version, it is delivered including head harness, buckles and neck straps. But if it is ordered together with "Pre-delivery mounting of helmet adapter" it is delivered without head harness, buckles and neck strap.

Technical specifications

Approval: CE 89/686/EEC	Standard: EN 136 / EN 137- type 2
Material: Natural rubber / Silicone (only M/L)	Material (2): Visor - Polycarbonate
Connection : Quick connection to breathing valve	Weight: 0,7 kg

