

SGT Docking Station

100414

Bump testing portable monitors is becoming more and more prevalent in the market.

Ensuring sensors are responding to a known concentration of gas remains the best way to verify the monitor has not become impeded. The Clip SGT docking station provides bump testing, event management and calibration from a simple to use multi-unit station and gives fleet or safety managers the ability to update configurations on large fleets. It also maintains the all important event logs that demonstrate users are working within company requirements.

Technical specifications

Size	47 x 41 x 22cm (18.50 x 16.14 x 8.66 in.)
Weight (Without gas cylinder)	8.2kg
Operating Temperature	41 to + 104°F (5 to + 40°C)
Warranty	Full 2 years
Battery Type	Rechargeable Lithium-Ion
Battery Life	1000 Bump Tests
LEDs	5 red / green / orange LEDs (1 for each unit, 1 for power)
Memory	USB 8GB Standard
Log Capacity	Approximately Up to 10 million tests (8GB, removable USB memory)
Tests Performed	Bump Test and Calibration
Information Stored	Bump/Cal Logs, Individual Monitor Event Logs, Firmware and Unit Configurations
Gases Available	CO, H ₂ S and CO ₂
Unit Compatibility	Works with SGT
Calibration Gas	Compatible with 58L cylinders
Charging Adaptor	12V, 3A

