

Spreader SP 5240 CL

100159

Lightweight, no concessions on performance:

- Easy to carry and handle
- Reducing physical burden
- Maximum performance at minimum weight

Effective profile on the spreading tips:

- Perfect grip in every situation

Ergonomic carrying handle:

- New design increases operator comfort in various working positions

New LED lighting in the carrying handle:

- No less than six LED lights with a higher light output
- Rescuers can start their job right away, both during the day and at night, without working in their own shadow

Built-in Speed Valve:

- When unloaded, the arms open quickly to the desired distance to speed up spreader positioning

New control handle:

- Improved ergonomic design, offering better grip for optimal tool control

Technical specifications

Details		
Articlenumber	150.012.322	
Basic specifications		
model	SP 5240 CL	
equipped with (connector type)	CORE	
max. working pressure	720 / 72 (bar/Mpa)	10443 psi

Performance		
max. spreading force	131 / 13.4 (kN/t)	29450 lbf
min. spreading force (EN 13204)	40 / 4.1 (kN/t)	8992 lbf
spreading distance	510 mm	20.1 in
max. squeezing force	47 / 4.8 (kN/t)	10566 lbf
max. pulling force	47 / 4.8 (kN/t)	
directives	2006/42/EC	
Dimensions, weight and temperature		
weight, ready for use	9.6 kg	21.2 lb
dimensions (AxBxC)	685 x 274 x 207 mm	27 x 10.8 x 8.2 in
Norms		
NFPA 1936 compliant	yes	
NFPA 1936, HPF	47 / 4.8 (kN/t)	10566 lbf
NFPA 1936, HSF	53 / 5.4 (kN/t)	11915 lbf
NFPA 1936, LPF	24 / 2.4 (kN/t)	5395 lbf
NFPA 1936, LSF	35 / 3.6 (kN/t)	7868 lbf



