

Spreader SP 5240

100158

Lightweight, no concessions on performance:

- Easy to carry and handle
- Reducing physical burden
- Maximum performance at minimum weight

Effective profile on the spreading tips:

- Perfect grip in every situation

Ergonomic carrying handle:

- New design increases operator comfort in various working positions

New LED lighting in the carrying handle:

- No less than six LED lights with a higher light output
- Rescuers can start their job right away, both during the day and at night, without working in their own shadow

Built-in Speed Valve:

- When unloaded, the arms open quickly to the desired distance to speed up spreader positioning

New control handle:

- Improved ergonomic design, offering better grip for optimal tool control

Technical specifications

Details		
Articlenumber	150.012.323	
Basic specifications		
model	SP 5240	
equipped with (connector type)	CORE	
max. working pressure	720 / 72 (bar/Mpa)	10443 psi

Performance		
max. spreading force	280 / 28.6 (kN/t)	62947 lbf
min. spreading force (EN 13204)	41 / 4.2 (kN/t)	9217 lbf
spreading distance	725 mm	28.5 in
max. squeezing force	59 / 6 (kN/t)	13264 lbf
max. pulling force	47 / 4.8 (kN/t)	
directives	2006/42/EC	
Dimensions, weight and temperature		
weight, ready for use	14.5 kg	32 lb
dimensions (AxBxC)	815 x 286 x 217 mm	32.1 x 11.3 x 8.5 in
Norms		
EN 13204 classification	AS41/725-14.5	
NFPA 1936 compliant	yes	
NFPA 1936, HPF	47 / 4.8 (kN/t)	10566 lbf
NFPA 1936, HSF	70 / 7.1 (kN/t)	15737 lbf
NFPA 1936, LPF	25 / 2.5 (kN/t)	5620 lbf
NFPA 1936, LSF	38 / 3.9 (kN/t)	8543 lbf



