



Spreader SP 5280

100162

Lightweight, no concessions on performance:

- Easy to carry and handle
- Reducing physical burden
- Maximum performance at minimum weight

Effective profile on the spreading tips:

- Perfect grip in every situation

Ergonomic carrying handle:

- New design increases operator comfort in various working positions

New LED lighting in the carrying handle:

- No less than six LED lights with a higher light output
- Rescuers can start their job right away, both during the day and at night, without working in their own shadow

Built-in Speed Valve:

- When unloaded, the arms open quickly to the desired distance to speed up spreader positioning

New control handle:

- Improved ergonomic design, offering better grip for optimal tool control

Technical specifications

Details		
Articlenumber	150.012.326	
Basic specifications		
model	SP 5280	
equipped with (connector type)	CORE	
max. working pressure	720 / 72 (bar/Mpa)	10443 psi

Performance		
max. spreading force	463 / 47.2 (kN/t)	104087 lbf
min. spreading force (EN 13204)	83 / 8.5 (kN/t)	18659 lbf
spreading distance	662 mm	26.1 in
max. squeezing force	159 / 16.2 (kN/t)	35745 lbf
max. pulling force	99 / 10.1 (kN/t)	
directives	2006/42/EC	
Dimensions, weight and temperature		
weight, ready for use	19.4 kg	42.8 lb
dimensions (AxBxC)	801 x 322 x 220 mm	31.5 x 12.7 x 8.7 in
Norms		
EN 13204 classification	CS83/662-19.4	
NFPA 1936 compliant	yes	
NFPA 1936, HPF	99 / 10.1 (kN/t)	22256 lbf
NFPA 1936, HSF	142 / 14.5 (kN/t)	31923 lbf
NFPA 1936, LPF	53 / 5.4 (kN/t)	11915 lbf
NFPA 1936, LSF	74 / 7.5 (kN/t)	16636 lbf



