Help and Support
+385 1 6553 655
info@vatropromet.hr

Stable Coupling 75 mm "B", Internal Thread 2,5"

1033123

Stable couplings can be installed on firefighting equipment that connects to pipes (nozzles, valves, hydrants, manifolds, busbars, suction baskets ...). Storz quick-release couplings are divided into inner and outer threaded couplings and fabricated into aluminium and stainless steel materials.

Technical specifications


Materials:

- Cast in aluminium alloy AK 11 (AlSi 11)
- Gasket - Rubber

Nominal size	a (mm)	b (mm)	d (mm)	L (mm)	L_1 (mm)	G	Seal ability on overpressure (Mpa)	Seal ability on underpressure (Mpa)	Weight (kg)
25	55	31	18	28	15	G1	1,6	2,5	0,08
52	98	66	44,5	36	19	G2	2,6	3,5	0,24
52	98	66	44,5	36	19	$G_{1/2}$	2,6	3,5	0,24
75	126	89	64,5	40	25	$G2_{1/2}$	2,6	3,5	0,40
75	126	89	64,5	40	25	G3	2,6	3,5	0,40
110	182	133	100	46	27	G4	2,6	3,5	0,91
110	182	133	100	46	27	$G4_{1/2}$	2,6	3,5	0,91






a
b
d
T
T1
G