

Submersible Pump for clear water Pedrollo Top Floor 2

1007443

The TOP-FLOOR series is suitable for use with clear water that does not contain abrasive particles. As a result of their ability to drain water to a level of 2 millimetres above ground level, they are suitable for use in domestic emergencies where a small area must be drained to the lowest level possible.

Application Limits:

- 3m maximum immersion depth
- Maximum liquid temperature +40 Degree
- Passage of suspended solids up to 2 mm
- Suction down to 2 mm above ground level
- Continuous service S1

Technical specifications

- Liquid type: clean Water
 - Uses: domestic
 - Applications: drainage, emptying tanks
 - Typology: submersible
 - Family: submersible pumps
 - Flow rate up to 160 l/min (9,6 m³/h)
 - Head up to 9 m
 - Temperature of the liquid to +40 °C
 - Pump body: Technopolymer
 - Suction Filter: Technopolymer
 - Suction Plate: Stainless steel AISI 304
 - Diffuser: Technopolymer
 - Impeller: Noryl FE1520PW
 - Motor Casing: Stainless steel AISI 304
 - Motor Casing Plate: Stainless steel AISI 304
 - Motor Shaft: Stainless steel EN 10088-3 - 1.4104
 - Lip Seal: 12 x 19 x 5 mm
-
- [Download Datasheet 50Hz](#)
 - [Download Datasheet 60Hz](#)

